

CORDED GRINDERS & SANDERS



ANGLE GRINDERS

- Compact, lightweight design
- 750 MWO motor: Powerful for daily applications
- Debris baffles: Protect internal components by deflecting damaging debris out of the airflow at the intake vents
- Multi-port exhaust: Reduces motor burn-up by efficiently venting hot air out of the grinder
- Tool free, burst resistant guard: The only grinder in its class with a tool free guard
- Compatible with multiple grinder guards and flanges
- Includes: Type 27 guard, side handle and spanner wrench

Model No. TLV064
Mfg. No. 6130-33
Price/Each \$

SPECIFICATIONS

Wheel Diameter: 4 1/2"
Voltage: 120 V
Amperage: 7.0
No Load RPM: 11 000
Spindle Size: 5/8"-11
Tool Weight: 3.5 lbs.



ANGLE GRINDERS

- Powerful 11 Amp, 11 000 RPM motor: Provides maximum performance and durability
- Overload protection: Maximizes motor life
- Electronic clutch: Extends tool life and prevents bind-up
- Tool-free accessory change: Easily change "All Accessories" without a wrench
- Tool-free adjustable guard: Provides quick guard installations and adjustments
- Trigger grip handle: Provides better control, reach and leverage
- Includes: Type 27 guard, side handle, spanner wrench, flanges

Model No. TLV734
Mfg. No. 6121-31
Price/Each \$

SPECIFICATIONS

Wheel Diameter: 4 1/2"
Voltage: 120 V
Amperage: 11.0
No Load RPM: 11 000
Spindle Size: 5/8"
Tool Weight: 5.4 lbs.



4-1/2" ANGLE GRINDERS

- Dust Ejection System™ provides durability by ejecting damaging dust and debris particles
- Large spiral bevel gear provides long transmission life
- One-Touch™ Guard allows for 360° rotation of the guard with a single action
- Paddle switch with safety lock-off prevents accidental start up
- Includes: 2-position side handle and One-Touch™ Guard

Model No. TYL343
Mfg. No. DWE402
Price/Each \$

SPECIFICATIONS

Wheel Diameter: 4 1/2"
Voltage: 120 V
Amperage: 11.0
No Load RPM: 11 000
Spindle Size: 5/8"-11
Tool Weight: 4.6 lbs.



ANGLE GRINDERS W/CASE

- Labyrinth construction seals motor and bearings from contamination
- Thumb switch conveniently located for operator comfort
- Ergonomic soft grip for vibration absorption and comfortable operation
- Slim housing design for easy handling and maneuverability
- Includes: Grinding wheel, lock nut, lock nut wrench, inner flange, wheel cover assembly and plastic carrying case

Model No. TLV165
Mfg. No. GA4530K
Price/Each \$

SPECIFICATIONS

Wheel Diameter: 4 1/2"
Voltage: 120 V
Amperage: 6.0
No Load RPM: 11 000
Spindle Size: 5/8"
Tool Weight: 4.0 lbs.



ANGLE GRINDERS

- Super Joint System II reduces vibration and prevents kickback during wheel lock up
- Constant speed control maintains constant speed under heavy load
- Labyrinth construction features a series of channels to prevent penetration of dust and debris into the field and armature
- Rotatable gear housing can be positioned at every 90° for optimal positioning
- Includes: Depressed centre wheel, anti-vibration side handle, lock nut wrench, toolless wheel cover, inner flange and lock nut

Model No. TYL234
Mfg. No. GA4542C01
Price/Each \$

SPECIFICATIONS

Wheel Diameter: 4 1/2"
Voltage: 120 V
Amperage: 12.0
No Load RPM: 2800-11 000
Spindle Size: 5/8"-11
Tool Weight: 5.5 lbs.



ANGLE GRINDERS

- Powerful 7.5 Amp, 10 000 RPM motor: Provides maximum performance and durability
- Overload protection: Maximizes motor life
- Electronic clutch: Extends tool life and prevents bind-up
- Tool-free accessory change: Easily change all accessories without a wrench
- Tool-free adjustable guard: Provides quick guard installations and adjustments
- Includes: 4 1/2" grinding wheel, wheel guard, lock nut, lock nut wrench, side handle and inner flange

Model No. TGZ314
Mfg. No. 9557NB
Price/Each \$

SPECIFICATIONS

Wheel Diameter: 4 1/2"
Voltage: 120 V
Amperage: 7.5
No Load RPM: 10 000
Spindle Size: 5/8"
Tool Weight: 4.5 lbs.



MINI-GRINDER™

- Safety clutch eliminates backlash
- Exclusive Quick feature for tool-free wheel change
- Includes: Side handle

Model No. TD920
Mfg. No. 30-A-161
Price/Each \$

SPECIFICATIONS

Wheel Diameter: 4 1/2"
Voltage: 120 V
Amperage: 8.0
No Load RPM: 10 000
Spindle Size: 5/8"
Tool Weight: 4.0 lbs.

