## 3/8" HEAVY-DUTY AIR RATCHET WRENCHES

- · Lightweight aluminum design minimizes operator fatigue
- Polyurethane grip reduces vibration
- Variable speed, reversible

auroratools°

- Paddle style trigger provides better speed control
- Ideal for automotive and industrial fastener removal and installation work

#### Model No. THZ671



## 1/2" HEAVY-DUTY AIR RATCHET WRENCHES

- · Lightweight aluminum design minimizes operator fatigue
- Polyurethane grip reduces vibration
- Variable speed, reversible
- · Paddle style trigger provides better speed control
- · Ideal for automotive an industrial fastener removal and installation work

#### Model No. TH7680



## *auroratools*°

	S	<b>luare</b>			Average			Vibration					
		rive	Free	Torque	Air		Hose	Horse	Less	Sound	Ne		
Model		Size	Speed	Range	Consumption	Air	Size	Power	Than	Pressure	Weig	ght	Price
No.	in	mm	RPM	ft-lbs.	CFM	Inlet	in mm	HP	m/s²	Level dB(A)	lbs.	kg	/Each
THZ671	3/8	9.5	175	5-75	3	1/4" - 18 NPT	3/8 9.5	0.45	1.0	78	2.6	1.18	
THZ680	1/2	12.7	175	5-75	3	1/4" - 18 NPT	3/8 9.5	0.45	1.0	83	2.6	1.18	

## 1/4" STUBBY TYPE AIR RATCHET WRENCHES

- · Lightweight aluminum design minimizes operator fatigue
- Polyurethane grip reduces vibration
- Variable speed, reversible
- Paddle style trigger provides better speed control
- Powerful tool in a compact design
- (Polyurethane handle helps insulate vibration)
- Overall length: 7 1/4"
- Weight: 1.4 lbs.

## Model No. TLZ140



	Square	Free	Torque	Average Air		Hose	Vibrations	Sound	
Model	Drive	Speed	Range	Consumption	Air	Size	Size Less Than		Price
No.	in mm	RPM	ft-lbs.	CFM	Inlet	in mm	m/s²	Level dB(A)	/Each
TLZ140	1/4 6.35	230	5-30	3	1/4" - 18 NPT	5/16 8	4.4	87	

## **RATCHETS**

## 1/4" RATCHETS

#### For light duty repair or assembly work

- Also for confined space or
- hard to reach areas
- 1/4" square drive spindle with pin retainer
- Reverse button
- · Ball-type socket retainer
- Teasing throttle
- 1/4" (NPTF) air inlet

Model No. THZ865



## 3/8" RATCHETS

#### For assembly, including electronics, appliances, and light manufacturing

- Fast change, 3/8" square drive spindle
- Improved ratchet head
- Reverse button
- · Use as hand ratchet for final torque up or to break fastener loose
- 1/4" (NPTF) air inlet

Model No. THZ869





## 1/2" RATCHETS

For assembly, including electronics, appliances, and light manufacturing

- Fast change, 1/2" square drive spindle
- Improved ratchet head
- Reverse button
- Use as hand ratchet for final
- torque up or to break fastener loose
- 1/4" (NPTF) air inlet

Model No. TG069



# Chicago Pneumatic™

Torque								Head Dimensions					
		Square	Free	Rai	nge				Ht. To		Overall	Net	
Model	Mfg	Drive	Speed	FtIbs. (Nm)				Vibration	Rear of	Side to	Length	Weight	Price
No.	No.	in.	RPM	Min.	Max	CFM	dBA	m/s²	Socket in. (mm)	Centre in. (mm)	in. (mm)	lbs. (kg)	/Each
THZ865	CP825C	1/4	280	4 (5)	18 (25)	15.5	82	10	1 5/16 (24)	1 19/32 (15)	6 3/5 (169)	1.1 (.5)	
THZ869	CP828	3/8	150	10 (14)	50 (68)	16	92	10	1 3/16 (30.2)	25/32 (19.8)	10 (254)	2.6 (1.2)	
TG069	CP828H	1/2	150	10 (14)	50 (68)	16	92	10	1 3/16 (30.2)	25/32 (19.8)	10 (254)	2.6 (1.2)	

Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1. For initial loosening and final tightening, apply torque by hand, not to exceed 30 ft.-lbs. (41 Nm)