

3" AIR CUT-OFF TOOLS

- Polyurethane handle reduces operator fatigue and vibration
- Power/speed regulator allows for easy PSI adjustment
- Twin-bearing design for smooth operation and cut off powerfully
- Wrench and Allen Key included to lock/unlock the disc
- Cut off wheel dimensions compatible with tool is 3" diameter x 0.060" thick (or thicker) x 3/8" arbour

Model No. THZ677



aurora tools

Model No.	Cutting Wheel		Free Speed RPM	Average Air Consumption		Hose Size		Horsepower HP	Vibration Less Than m/s ²	Sound Pressure Level dB(A)	Net Weight		Price /Each
	in	mm		CFM	Air Inlet	in	mm				lbs.	kg	
THZ677	3	76.2	21 000	3	1/4"-18 NPT	3/8	9.5	0.45	0.2	81	1.8	0.82	

AIR CUT-OFF TOOL

- Prevents accidental throttle operation by utilizing a spring-loaded latch that resets each time the lever is released
- Disk Diameter: 2-7/8"
- Wheel Type: 41
- Maximum Wheel Thickness: 1/8"



IR
Ingersoll Rand

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	No Load RPM	Price /Each
BW385	326	10 CFM	1/4" NPTF	107.3	20000	

PNEUMATIC HEAVY-DUTY RECIPROCATING AIR SAW KIT

- Heavy duty kit includes CP's 7901 reciprocating saw plus (5) each replacement blades: 18T, 24T, 32T packed in a heavy duty carrying case
- Lowest vibration on the market to reduce operator fatigue
- Adjustable guide offers flexibility in setting depth of cut
- Swivel included
- Ergonomic design for comfort and easy handling
- Product Type: Pneumatic
- Working pressure: 10000
- O.A.Length": 9
- Housing Material: Metal and Composite
- Recommended Air Pressure (psi): 90



CP Chicago Pneumatic™

Model No.	Mfg. No.	Air Inlet	Sound Level (dBA)	Strokes per Min.	Stroke Length"	Price /Each
THZ855	8941079010	1/4" NPT	78	10000	3/8	

AIR RECIPROCATING SAWS

- Prevents accidental throttle operation by utilizing a spring-loaded latch that resets each time the lever is released
- Inline configuration allows for easier access in tight spaces



BW397

IR
Ingersoll Rand

Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Strokes per Min.	Stroke Length	Price /Each
BW397	429	8 CFM	1/4" NPTF	100.3	10000	3/8"	
BW398	4429	4 CFM	1/4" NPTF	66.2	5750	3/8"	



BW398