
VISES, MAGNETS & CLAMPS

VERTICAL HOLD-DOWN CLAMPS

The most popular type of hold-down clamp, manufactured in capacities of up to 6000 lbs.

The hold-down bar exhibits a minimum 90° opening angle and can be solid or U-shaped.

Stainless steel units are available for the food industry or corrosive environments.



201 SERIES

The smallest vertical clamp available. U-shaped hold-down bar furnished with bonded neoprene-tipped 10-32 spindle assembly (TN140) and flanged washers (TN121).



207 SERIES

Available in solid bar model, including bolt retainer (TN141) 500-lb.-capacity. U-bar model includes two flanged washers (TN125) and accommodates 5/16" spindle (not supplied).



202 SERIES

200-lb. capacity version of 201 series. Furnished with bonded neoprene-tipped 1/4-20 spindle (TN134) lock nuts and flang washers (TN123).



210 SERIES

Heavy-duty clamp holds up to 750 lbs. U-bar model includes two flanged washers (TN124). Bolt retainer supplied with solid bar models (TN142) accommodates any 3/8" spindle (not supplied).



Model	Mfg.	Holding			Base			Wt.	Price		
No.	No.	Cap. lbs.	A	В	C	D	L"	X	W"	lbs.	/Each
TN059	201-U	100	3 1/16	2 1/64	11/16	5/8	1	Х	1 5/16	0.15	
TN061	202-U	200	3 3/4	2 3/8	1	15/16	1	Х	1 9/16	0.35	
TN065	207-S	500	5 1/2	3 25/32	-	1 9/16	13/8	χ	1 3/4	0.69	
TN064	207-U	375	5 1/2	3 25/32	13/8	1 9/16	13/8	X	1 3/4	0.67	
TN066	210-U	600	7 1/2	5 7/8	2 5/8	1 11/16	1 29/32	X	2 17/32	1.29	
TN067	210-S	750	7 1/2	5 7/8	-	1 11/16	1 29/32	X	2 17/32	1.29	

TOGGLE-LOCK PLUS™ LATCH CLAMPS

Feature a release lever catch accessory which allows clamps to lock in the closed position only. Supplied with latch plate and equipped with an ergonomic handle grip. Model TV727 same as model TV726 only with greater holding capacity.

Model	Mfg.	Holding	Dimensions"		Thread	Base			Drawing	Wt.	Price
No.	No.	Cap. lbs.	A	В	Adjustment"	L"	X	W"	Cap."	lbs.	/Each
TV726	331-R	700	1 15/32	6 1/4	11/64	1 9/16	Х	13/4	2	0.6	
TV727	341-R	2000	2 3/4	6 1/2	9/16	23/8	Х	23/8	2 1/2	0.6	



Equipped with a release lever catch accessory which allow clamps to stay locked in the closed position. Large handle pad improves operation of clamp.


Model	Mfg.	Holding	Dimensions"		Thread		Base		Drawing	Wt.	Price
No.	No.	Cap. lbs.	A	В	Adjustment"	L"	X	W"	Cap."	lbs.	/Each
TV728	351-R	375	1 7/16	9 11/16	5/16	1 1/2	Х	1 15/16	4	0.8	
TV729	371-R	750	2 1/4	13	11/16	1 15/16	Х	1 15/16	5 3/8	0.6	





HORIZONTAL HOLD-DOWN CLAMPS

Low height design makes clamps outstanding when headroom is a concern. Unlike the handle on the vertical clamp, the horizontal clamp moves in the opposite direction. Hold down bar available in solid or U-shaped format. Some models available in stainless steel on request. Holding capacities to 500 lbs. Larger capacities available.



205 SERIES

215 & 225 SERIES

tipped spindle assembly (TN134) and washers (TN123). The 225 Series includes a 5/16-18 bonded neoprene spindle assembly (TN135) and flanged washers (TN125).

The smallest clamps in the horizontal series clamps supplied with nylon spindle assembly (TN126). Flanged washers supplied with U-bar models (TN122).

U-bar horizontal clamps provide greater rigidity and overall performance. The 215 Series includes a 1/4-20 bonded neoprene-



305 SERIES

Feature a handle that can be operated from either side or from behind. U-bar model includes bonded neoprene-tipped spindle (TN140) and flanged washers (TN121).





Model	Mfg. Holding			Dimensions"				Base			Price
No.	No.	Cap. lbs.	A	В	C	D	L"	X	W"	lbs.	/Each
TN062	205-U	60	3/4	2 21/32	3/8	5/16	15/16	Х	15/16	0.06	
TN063	205-S	60	3/4	23/4	-	3/8	15/16	Х	15/16	0.06	
TN068	215-U	200	1 1/2	5 7/16	1 1/4	1	1 7/16	Х	1 3/8	0.32	
TN069	225-U	500	1 7/8	6 19/32	1 11/32	1 3/8	1 1/2	Х	1 3/8	0.55	
TN070	305-U	150	1 3/8	2 1/4	1/2	1/2	1 1/32	Х	1	0.13	